

DESCRIPTION	A water-based polyurethane two-component varnish for use with Cameleo decorative effects.
COLOUR	White, colorless after drying.
METHOD OF TINTING	Lack
SURFACE PREPARATION	The preparation of the substrate should be in line with the specific Cameleo decorative effect.
PRODUCT PREPARATION	Before use, it must be mixed with the HARDENER additive (H02). It is best to mix manually for about 5 minutes, or mechanically at low speed for about 1 minute. Remember not to air the varnish during mechanical mixing. After mixing with the HARDENER additive (H02), the varnish should be used within 5 hours. The HARDENER additive should not exceed 10% of the varnish volume. The varnish can be diluted with water up to 10% of its volume.
APPLICATION	Paint roller (microfiber), brush, microfiber mop. The impregnation should be applied to the previously prepared Cameleo decorative surface.
TECHNICAL DATA	
Thinner:	Water
Specific weight:	1.04 g/ml
Efficiency to:	0.110 l/m ² (2 layers for Stone Effect Classic Effect)
Practical efficiency:	The yield depends on many factors such as the porosity and roughness of the substrate and material losses during application.
pH:	Approx. 8.6
PRODUCT DRYING TIME	At the temperature of 20°C and 50% air humidity.
Dry to the touch:	4 hours after application
Hardening:	7 days after application
CLEANING TOOLS	Warm soapy water.
CLEANING AND CARE OF THE SURFACE	It is possible to clean the surface after 14 days from the end of the full application. Do not use detergents. Clean with soap and water.
APPLICATION CONDITIONS	Application temperature +10°C - +30°C. The minimum temperature of the substrate: +10°C. Maximum substrate temperature: +30°C. Substrate humidity should not exceed 4%. Maximum air humidity: 75%. In the case of application on substrates with underfloor heating, they should be extinguished beforehand, min. 3 days before starting the application.
STORAGE AND TRANSPORT	Store in a tightly closed container at a temperature of +5°C - +25°C. Product sensitive to frost. Protect against sunlight. Shelf life: 12 months from the production date in original sealed packaging (production date on the packaging).
PACKAGING	0.8 l, 2.4 l, 10.4 l
APPROVALS/NORMS	PN-C-81802
SAFETY INSTRUCTIONS	All product safety indications are available in the Safety Data Sheet.
VOC	86.6 g/l
VOC category	A/e
VOC limit	130 g/l
COMMENTS	Before use, the product should be thoroughly mixed manually or mechanically. When working on planes larger than those provided for in the capacity of a unit package, it is necessary to mix the contents of unit packages in one collective package. The colors shown in the catalog may differ from the actual colors on the wall. The colors depend on the method of application, texture, gloss, lighting, sunlight, and the types and intensity of other colors in the environment. The conditions of storage, transport and use as well as the end result are beyond our control and therefore cannot constitute a guarantee in the legal sense. In any case, the statutory provisions and any rights of third parties must be observed.

WARRANTY

Cameleo Leśniewicz Gradkowska Spółka Jawna guarantees that Cameleo products are of commercial quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty, provided that they are used in accordance with the instructions contained in the Technical Data Sheet of the Product. Products are not covered by the warranty if they are not used in accordance with the information contained in the Technical Data Sheet of the Product. Liability under this warranty (if the product turns out to be defective) is limited only to the replacement of the product or the refund of the purchase price of the product. This warranty is valid for one year from the purchase of the product.

UPDATE DATE 28-02-2022