

DESCRIPTION	A priming impregnate used as a base for Cameleo decorative effects.
COLOUR	Milky
SURFACE PREPARATION	
Unapainted surface	Fresh cement, cement-lime plasters and new concrete substrates should be seasoned for not less than 30 days. Allow gypsum surfaces to dry completely. Be sure to remove dirt, dust, grease stains. Plasterboard, unevenness of the base, smooth out cracks.
Painted surface	Remember to remove dirt, dust, grease stains, glue residues. The entire surface is matted with sandpaper, grain size 120 - 150. Unevenness of the substrate, smooth out cracks.
PRODUCT PREPARATION	Mix by hand. Do not dilute. The product is ready for use.
APPLICATION	Paint roller, brush. The substrate to be painted with CAMEPRIMER P100 primer should be painted once or twice.
TECHNICAL DATA	
Thinner:	Water
Specific weight:	1.00 g/ml
Efficiency to:	0.115 l/m ²
Practical efficiency:	Efficiency depends on many factors such as porosity and roughness of the substrate and material losses during application.
pH:	Approx. 8.6
PRODUCT DRYING TIME	At the temperature of 20°C and 50% air humidity.
Dry to the touch:	2 hours after application
CLEANING TOOLS	Warm soapy water.
APPLICATION CONDITIONS	Application temperature +10°C - +30°C. The minimum temperature of the substrate: +10°C. Maximum substrate temperature: +30°C. Substrate humidity should not exceed 4%. Maximum air humidity: 75%.
STORAGE AND TRANSPORT	Store in a tightly closed container at a temperature of +5°C - +25°C. Product sensitive to frost. Protect against sunlight. Shelf life: 12 months from the production date in original sealed packaging (production date on the packaging).
PACKAGING	0.8 l, 2.4 l, 10.4 l
CERTIFICATES/NORMS	PN-C-81906 type III
SAFETY INSTRUCTIONS	All product safety indications are available in the Safety Data Sheet.
VOC	22 g/l
VOC category	A/g
VOC limit	30 g/l
COMMENTS	The product should be thoroughly mixed by hand before use. When working on planes larger than those provided for in the capacity of a unit package, it is necessary to mix the contents of unit packages in one collective package. The colors shown in the catalog may differ from the actual colors on the wall. The colors depend on the method of application, texture, gloss, lighting, sunlight, and the types and intensity of other colors in the environment. The conditions of storage, transport and use as well as the end result are beyond our control and therefore cannot constitute a guarantee in the legal sense. The statutory provisions and any rights of third parties must always be observed.
WARRANTY	Cameleo Leśniewicz Grądkowska Spółka Jawna guarantees that Cameleo products are of commercial quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty, provided that they are used in accordance with the instructions contained in the Technical Data Sheet of the Product. Products are not covered by the warranty if they are not used in accordance with the information contained in the Technical Data Sheet of the Product. Liability under this warranty (if the product turns out to be defective) is limited only to the replacement of the product or the refund of the purchase price of the product. This warranty is valid for one year from the purchase of the product.
UPDATE DATE	28-02-2022

