

DESCRIPTION	Primer paint used as a base for Cameleo decorative effects.
COLOUR	White base
METHOD OF TINTING	Possibility of tinting with Cameleo pigments.
SURFACE PREPARATION	
Unpainted surface	Fresh cement and cement-lime plasters and new concrete substrates should be seasoned for at least 30 days. Allow gypsum surfaces to dry completely. Be sure to remove dirt, dust, grease stains. Gypsum plasterboards, smooth out any unevenness in the substrate, and even out cracks, then apply a primer to the whole surface with CAMEPRIMER P100 primer.
Painted surface	Remember to remove dirt, dust, grease stains, glue residues. The entire surface is matted with sandpaper, grain size 120 - 150. Unevenness of the substrate, smooth out cracks.
PRODUCT PREPARATION	
	Stir manually or mechanically. Do not dilute. The product is ready for use. In the case of painting the surface with the CAMEPRIMER P300 primer paint with the addition of the Cameleo pigment, the product should be thoroughly mixed in order to make the paint color uniform. When working on planes larger than those provided for in the capacity of a unit package, it is necessary to mix the contents of unit packages in one collective package.
APPLICATION	
	Paint roller, brush. The substrate to be painted with CAMEPRIMER P300 primer paint should be painted once or twice.
TECHNICAL DATA	
Thinner:	Water
Specific weight:	1.38 g/ml
Efficiency to:	0.115 l/m ²
Practical efficiency:	Efficiency depends on many factors such as porosity and roughness of the substrate and material losses during application.
pH:	Approx. 8.6
PRODUCT DRYING TIME	
	At the temperature of 20°C and 50% air humidity.
Dry to the touch:	2 hours after application
CLEANING TOOLS	
	Warm soapy water.
APPLICATION CONDITIONS	
	Application temperature +10°C - +30°C. The minimum temperature of the substrate: +10°C. Maximum substrate temperature: +30°C. Substrate humidity should not exceed 4%. Maximum air humidity: 75%.
STORAGE AND TRANSPORT	
	Store in a tightly closed container at a temperature of +5°C - +25°C. Product sensitive to frost. Protect against sunlight. Shelf life: 12 months from the production date in original sealed packaging (production date on the packaging).
PACKAGING	
	0.8 l, 2.4 l, 10.4 l
CERTIFICATES/NORMS	
	PN-C-81906 type II
SAFETY INSTRUCTIONS	
	All product safety indications are available in the Safety Data Sheet.
VOC	12 g/l
VOC category	A/g
VOC limit	30 g/l
COMMENTS	
	Before use, the product should be thoroughly mixed manually or mechanically. When working on planes larger than those provided for in the capacity of a unit package, it is necessary to mix the contents of unit packages in one collective package. The colors shown in the catalog may differ from the actual colors on the wall. The colors depend on the method of application, texture, gloss, lighting, sunlight, and the types and intensity of other colors in the environment. The conditions of storage, transport and use as well as the end result are beyond our control and therefore cannot constitute a guarantee in the legal sense. The statutory provisions and any rights of third parties must always be observed.

WARRANTY

Cameleo Leśniewicz Gradkowska Spółka Jawna guarantees that Cameleo products are of commercial quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty, provided that they are used in accordance with the instructions contained in the Technical Data Sheet of the Product. Products are not covered by the warranty if they are not used in accordance with the information contained in the Technical Data Sheet of the Product. Liability under this warranty (if the product turns out to be defective) is limited only to the replacement of the product or the refund of the purchase price of the product. This warranty is valid for one year from the purchase of the product.

UPDATE DATE 28-02-2022