

DESCRIPTION	Epoxy primer paint used as a base for the Cameleo floor decorative effects.
COLOUR	White
SURFACE PREPARATION	Before applying the Cameleo decorative effect, the surface of the substrate should be properly prepared.
Concrete substrates:	The concrete substrate should be seasoned for not less than 30 days, and the humidity should not exceed 4%. The class of the concrete substrate should not be less than C20/25 (B25). Any contamination and dirt must be removed mechanically. The prepared surface should be primed once with CAMEPRIMER P100 primer.
Substrates on glazed tiles:	The substrate made of glazed and porcelain tiles should be roughened using a grinder and a diamond disc. The substrate prepared in this way should be primed with the CAMEPRIMER P100 primer.
PRODUCT PREPARATION	Mix manually or mechanically in the proportion: 2.4 kg part A + 0.6 kg part B + 1,5 kg part C or 9.6 kg part A + 2.4 kg part B + 6 kg part C
APPLICATION	Venetian trowel
TECHNICAL DATA	
Thinner:	Water
Specific weight:	1.34 g/ml (with the addition of D.E.R.™ 3221 Epoxy Resin in a ratio of 4:1)
Efficiency to:	0.6 kg/m ²
Practical efficiency:	Efficiency depends on many factors such as porosity and roughness of the substrate and material losses during application.
pH:	Approx. 9 (with the addition of D.E.R.™ 3221 Epoxy Resin in a ratio of 4:1)
PRODUCT DRYING TIME	At the temperature of 20°C and 50% air humidity.
Dry to the touch:	8 hours after application
CLEANING TOOLS	Warm soapy water.
APPLICATION CONDITIONS	Application temperature +10°C - +30°C. The minimum temperature of the substrate: +10°C. Maximum substrate temperature: +30°C. Substrate humidity should not exceed 4%. Maximum air humidity: 75%. In the case of application on substrates with underfloor heating, they should be extinguished beforehand, min. 3 days before starting the application.
STORAGE AND TRANSPORT	Store in a tightly closed container at a temperature of +5°C - +25°C. Product sensitive to frost. Protect against sunlight. Shelf life: 12 months from the production date in original sealed packaging (production date on the packaging).
PACKAGING	2.4 kg part A + 0.6 kg part B + 1,5 kg part C 9.6 kg part A + 2.4 kg part B + 6 kg part C
SAFETY INSTRUCTIONS	All product safety indications are available in the Safety Data Sheet.
VOC category	A/g
COMMENTS	Before use, the product should be thoroughly mixed manually or mechanically. When working on planes larger than those provided for in the capacity of a unit package, it is necessary to mix the contents of unit packages in one collective package. The colors shown in the catalog may differ from the actual colors on the wall. The colors depend on the method of application, texture, gloss, lighting, sunlight, and the types and intensity of other colors in the environment. The conditions of storage, transport and use as well as the end result are beyond our control and therefore cannot constitute a guarantee in the legal sense. The statutory provisions and any rights of third parties must always be observed.
WARRANTY	Cameleo Leśniewicz Grądkowska Spółka Jawna guarantees that Cameleo products are of commercial quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty, provided that they are used in accordance with the instructions contained in the Technical Data Sheet of the Product. Products are not covered by the warranty if they are not used in accordance with the information contained in the Technical Data Sheet of the Product. Liability under this warranty (if the product turns out to be defective) is limited only to the replacement of the product or the refund of the purchase price of the product. This warranty is valid for one year from the purchase of the product.

UPDATE DATE 28-02-2022