

<b>DESCRIPTION</b>	Decorative coating imitating the effect of patinated copper.
<b>COLOUR</b>	Brick-colored base
<b>METHOD OF TINTING</b>	Lack
<b>SURFACE PREPARATION</b>	Before applying the Cameleo decorative effect, the surface of the substrate should be properly prepared.
<b>Unapainted surface</b>	Fresh cement, cement-lime plasters and new concrete substrates should be seasoned for not less than 30 days. Allow gypsum surfaces to dry completely. Be sure to remove dirt, dust, grease stains. Gypsum plasterboards, smooth out any unevenness in the substrate, and even out cracks, then apply a primer to the whole surface with CAMEPRIMER P100 primer. Then paint with CAMEPRIMER P300 primer.
<b>Painted surface</b>	Remember to remove dirt, dust, grease stains, glue residues. The entire surface should be roughened with sandpaper, grain size 120 - 150. Smooth out any irregularities in the substrate, then even the whole surface once with the CAMEPRIMER P300 primer.
<b>PRODUCT PREPARATION</b>	Pour the contents of the package into an appropriate amount of water (30-35 % water per 1 KG). Mix everything thoroughly mechanically. When working on planes larger than those provided for in the capacity of a unit package, it is necessary to mix the contents of unit packages in one collective package. The product can be used up to 2 hours from mixing it with water.
<b>APPLICATION</b>	Venetian trowel, venetian trowel flex Single-layer plaster
<b>TECHNICAL DATA</b>	
<b>Thinner:</b>	Water
<b>Specific weight:</b>	1.9 g/ml (water content 33%)
<b>Efficiency to:</b>	Dry product: 0.4 kg/m <sup>2</sup>
<b>Practical efficiency:</b>	Efficiency depends on many factors such as porosity and roughness of the substrate and material losses during application.
<b>pH:</b>	Approx. 6.1 (water content 33%)
<b>PRODUCT DRYING TIME</b>	At the temperature of 20°C and 50% air humidity.
<b>Dry to the touch:</b>	6 hours after application
<b>Hardening:</b>	7 days after application
<b>CLEANING TOOLS</b>	Warm soapy water.
<b>RECOMMENDED PRIMERS</b>	CAMEPRIMER P100, CAMEPRIMER P300
<b>APPLICATION CONDITIONS</b>	Application temperature +10°C - +30°C. The minimum temperature of the substrate: +10°C. Maximum substrate temperature: +30°C. Substrate humidity should not exceed 4%. Maximum air humidity: 75%.
<b>STORAGE AND TRANSPORT</b>	Store in a tightly closed container at a temperature of +5°C - +25°C. Product sensitive to frost. Protect against sunlight. Shelf life: 12 months from the production date in original sealed packaging (production date on the packaging).
<b>PACKAGING</b>	2 kg, 10 kg
<b>SAFETY INSTRUCTIONS</b>	All product safety indications are available in the Safety Data Sheet.
<b>VOC</b>	0.2 g/l
<b>VOC category</b>	A/1
<b>VOC limit</b>	200 g/l
<b>Reaction to fire class</b>	B-s2, d0 (tabular value) Commission Delegated Regulation (EU) 2017/2018 of 20 March 2017

<b>COMMENTS</b>	<p>Before use, the product should be thoroughly mechanically mixed with a paint mixer. When working on planes larger than those provided for in the capacity of a unit package, it is necessary to mix the contents of unit packages in one collective package.</p> <p>The colors shown in the catalog may differ from the actual colors on the wall. The colors depend on the method of application, texture, gloss, lighting, sunlight, and the types and intensity of other colors in the environment.</p> <p>The conditions of storage, transport and use as well as the end result are beyond our control and therefore cannot constitute a guarantee in the legal sense. The statutory provisions and any rights of third parties must always be observed.</p>
<b>WARRANTY</b>	<p>Cameleo Leśniewicz Gradkowska Spółka Jawna guarantees that Cameleo products are of commercial quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty, provided that they are used in accordance with the instructions contained in the Technical Data Sheet of the Product.</p> <p>Products are not covered by the warranty if they are not used in accordance with the information contained in the Technical Data Sheet of the Product. Liability under this warranty (if the product turns out to be defective) is limited only to the replacement of the product or the refund of the purchase price of the product. This warranty is valid for one year from the purchase of the product.</p>
<b>UPDATE DATE</b>	28-02-2022