

DESCRIPTION	RUST & PATINA ACTIVATOR is an activating agent designed for the effects of patina (PATINA EFFECT) and rust (RUST EFFECT).
COLOUR	Blue (liquid form), blue-white (solid form)
SURFACE PREPARATION	The preparation of the substrate should comply with the specific decorative effect. Details of the application are available in the Technical Data Sheet of Effect.
PRODUCT PREPARATION	In liquid form, the product is ready to use after thorough mixing. In the case of solid form, fill the container with water and mix thoroughly. When working on surfaces larger than those provided for in the capacity of a unit package, it is necessary to mix the contents of unit packages in one collective package.
APPLICATION	RUST & PATINA ACTIVATOR is applied to the plaster surface with a dispenser. Details of the application are available on the website www.cameleo.pl and in the Technical Data Sheet of Effect.
TECHNICAL DATA	
Specific weight:	1.03 g/ml (liquid form)
Efficiency to:	0.1 l/m ²
VOC:	In accordance with the standard
pH:	Approx. 3.8 (liquid form)
PRODUCT DRYING TIME	At the temperature of 20°C and 50% air humidity.
Dry to the touch:	12 hours after application
Hardening:	21 days after application
CLEANING TOOLS	Warm soapy water.
CLEANING AND CARE OF THE SURFACE	It is possible to clean the surface after 21 days from the end of the full application. Do not use detergents. Clean with soap and water.
APPLICATION CONDITIONS	Application temperature +10°C - +30°C. The minimum temperature of the substrate: +10°C. Maximum substrate temperature: +30°C. Substrate humidity should not exceed 4%. Maximum air humidity: 75%.
STORAGE AND TRANSPORT	Store in a tightly closed container at a temperature of +5°C - +25°C. Product sensitive to frost. Protect against sunlight. Shelf life: 12 months from the production date in original sealed packaging (production date on the packaging).
PACKAGING	0.5 l
CERTIFICATES/NORMS	ZN-P-CM-032:2014
SAFETY INSTRUCTIONS	The product is classified as hazardous. All product safety instructions are available in the Safety Data Sheet.
COMMENTS	The product should be thoroughly mixed before use. When working on planes larger than those provided for in the capacity of a unit package, it is necessary to mix the contents of unit packages in one collective package. The colors shown in the catalog may differ from the actual colors on the wall. The colors depend on the method of application, texture, gloss, lighting, sunlight, and the types and intensity of other colors in the environment. The conditions of storage, transport and use as well as the end result are beyond our control and therefore cannot constitute a guarantee in the legal sense. The statutory provisions and any rights of third parties must always be observed.
WARRANTY	Cameleo Leśniewicz Grądkowska Spółka Jawna guarantees that Cameleo products are of commercial quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty, provided that they are used in accordance with the instructions contained in the Technical Data Sheet of the Product. Products are not covered by the warranty if they are not used in accordance with the information contained in the Technical Data Sheet of the Product. Liability under this warranty (if the product turns out to be defective) is limited only to the replacement of the product or the refund of the purchase price of the product. This warranty is valid for one year from the purchase of the product.
UPDATE DATE	28-02-2022

